



FEELING

CABLED CARDIGAN



Size: 12 (16)

NOTE: figures in brackets () refer to larger size. Where only one figure is given this refers to both sizes.

Skill Level: intermediate

How much yarn:

g 550 (650) of Feeling yarn, in blue n. 13653

Needles: Pair of 3.00 mm (no. 11) knitting needles

A spare needle. A Double-pointed (Dp) needle

Sewing needle: Yarn needle with rounded point

STITCHES

Using needles: reverse stocking st (rev st st)

Stocking stitch (st st).

CABLE: (worked on 9 sts)

Row 1 (RS): Knit. **Row 2 and every following even row:** Purl. **Rows 3:** Knit. **Row 5:** K3, 6 Left crossed stitches (= place next 3 sts onto Dp needle, on frontside, K next 3 sts, K3 from Dp needle). **Row 7:** 6 Right crossed stitches (= place next 3 sts onto Dp needle, on backside, K next 3 sts, K3 from Dp needle), K3. **Rows 9 and 11:** Knit. **Row 12:** Purl. Rep these 12 rows to form Cable.

TENSION

25 sts and 31 rows measure 10 cm square over rev st st and cables with 3.00 mm (no. 11) needles. Cable width: 3,5 cm.

INSTRUCTIONS

Back Lower Part: With 3.00 mm (no. 11) needles cast on 169 (181) sts. Work 4 rows in rev st st, then cont to work as follows: 10 (11) sts in rev st st, 9 sts in Cable motif, * 19 (21) sts in rev st st, 9 sts in Cable motif; rep from * 4 more times, 10 (11) sts in rev st st. Dec 1 st at either side of each Cable, on sts in rev st st (12 decs in total) on 13th row and every foll 20th row 3 more times: 121 (133) sts remain, between cables there are 11(13) sts and at et each end there are 6(7) sts. When piece measures cm 30 (32) cast off all sts.

Right Front Lower Part: With 3.00 mm (no. 11) needles cast on 76 (81) sts. Work 4 rows in rev st st, then cont to work as follows: 1st in rev st st, 9 sts in Cable motif, * 19 (21) sts in rev st st, 9 sts in Cable motif; rep from * once more, 10 (11) sts in rev st st. Dec 1 st only at inner side of first Cable (with 1 st at outer side) and dec 1 st at either side of rem 2 Cables, on sts in rev st st (5 decs in total) on 13th row and every foll 20th row 3 more times: 56 (61) sts remain, between cables there are 11(13) sts and at end there are 6 (7) sts. When piece

measures cm 30 (32) cast off all sts.

Left Front Lower Part: With 3.00 mm (no. 11) needles cast on 76 (81) sts. Work 4 rows in rev st st, then cont to work as follows: 10 (11) sts in rev st st, 9 sts in Cable motif, * 19 (21) sts in rev st st, 9 sts in Cable motif; rep from * once more, 1st in rev st st. Dec 1 st at either side of first 2 Cables, on sts in rev st st and dec only 1 st at inner side of last Cable (with 1 st at outer side) on 13th row and every foll 20th row (5 decs in total every time) 3 more times: 56 (61) sts remain, between cables there are 11(13) sts and at beg there are 6 (7) sts. When piece measures cm 30 (32) cast off all sts.

Right Sleeve and Upper Part: With 3.00 mm (no. 11) needles cast on 74 (80) sts and work as follows: 23 (25) sts in rev st st, 9 sts in Cable motif, 10 (12) sts in rev st st, 9 sts in Cable motif, 23 (25) sts in rev st st. Inc 1 st at each end on 9th row and every foll 12th (10th) row 11 (14) times. There are 98 (110) sts. When Sleeve measures 45 (47) cm from beg, cast on 51 (55) new sts at beg of next 2 rows for Front and Back: there are 200 (220) sts. Work first and last 13 (15) sts in rev st st, inside these sts work 9 sts in Cable motif; work rem sts in rev st st continuing to work the 2 Cable motifs of Sleeve. When piece mesures 13 (15)cm from last cast-on sts (for Front and Back), divide work for neck. Cont to work first 100 (110) sts of Front and leave rem 100 (110) sts of Back on a spare needle. Shape Front neck, dec 1 st on neck-side, inside 5 (6) sts in rev st st, on next and every other row 6 times, then every row 12 (14) times, ending the cable sts and working all sts in rev st st. When piece measures 9 cm from neck-shaping beg, cast off rem 82 (90) sts. Join yarn to rem 100 (110) sts of Back and continue to work, as established, for 11,5 cm more. Leave these sts on a spare needle.

Left Sleeve and Upper Part: Work as Right Sleeve and Upper Part reversing shaping.

FINISHING

With yarn needle and working yarn, graft in kitchener st the 2 Upper Parts in the middle of Back. Sew side seams of Lower Parts, then join Lower Parts to Upper Parts. Sew side seams, with cables in correspondence, and sleeve seams. **Opening borders (make 2):** with 3.00 mm (no. 11) needles, cast on 18 sts and work in rev st st until border measures as Front opening. Join border to opening side, then fold border in half and sew on WS of work.

